



Basic features

Additional features	Factor 1 Extended temperature range weld-immune (magnetic field 100kA/m) Housing resistant to weld spatter
Approval/Conformity	CE cULus EAC WEEE
Basic standard	IEC 60947-5-2
Scope of delivery	No nuts or lockwashers

Display/Operation

Function indicator	yes
Power indicator	no

Electrical connection

Connection	M12x1-Male, 3-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 µF
No-load current I_o max., damped	8.5 mA
No-load current I_o max., undamped	4.5 mA
Operating voltage U_b	10...30 VDC
Output resistance R_a	33.0 kOhm + D
Protection class	II
Rated insulation voltage U_i	250 V AC
Rated operating current I_e	200 mA
Rated operating voltage U_e DC	24 V
Rated short circuit current	100 A
Ready delay t_v max.	3 ms
Ripple max. (% of U_e)	15 %
Switching frequency	1500 Hz Measured at 2 mm, 24 V, 100 mA
Utilization category	DC -13
Voltage drop static max.	1.5 V

Environmental conditions

Ambient temperature	-30 °C...85 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP68
Magnetic field immune	magnetic field immune (AC/DC)

Functional safety

MTTF (40 °C)	379 a
---------------------	-------

Inductive Sensors
BES M12MI-PSC30A-S04G-W09
Order Code: BES05Y2

BALLUFF

Interface

Switching output PNP normally open (NO)

Material

Housing material Brass, PTFE coated
Material sensing surface PBT, PTFE coated

Mechanical data

Dimension $\varnothing 12 \times 65$ mm
Installation for flush mounting
Size M12x1
Tightening torque 12 Nm

Range/Distance

Assured operating distance Sa	2.4 mm
Hysteresis H max. (% of Sr)	15.0 %
Rated operating distance Sn	3 mm
Real switching distance sr	3 mm
Repeat accuracy max. (% of Sr)	5.0 %
Switching distance marking	■ ■
Temperature drift max. (% of Sr)	10 %
Tolerance Sr	± 10 %

Remarks

The sensor is functional again after the overload has been eliminated.
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams

